



Relationship notations



Pre-conference Workshop Paris, 2017-11-27

> Thorsten Niebuhr WedaCon GmbH





Refined Design principles of Identity Relationship Management

- Provable
 The exisitence of a given relation must be provable.
- Constrainable
 either part of the relation must be able to set a constraint on the use of the
 relationship.
- Mutable relationships might change, or be forever (A was made by B)
- Revocable
 The ending and revocation of relations
- Delegable Changing the actors
- Scalable be able to scale up to the very top of the view

See WG Doc on Identity Relationship Management





The onward journey

- Relationship Manager
 - Hard for the entities in a relation to manage their relation themself
 - Need for a managing ,instance' to orchestrate
- Relationship Notation
 - Standardized method to represent relationships





Notation ,Language⁴

- Notations
 - A system of [...] used to represent and express [...] facts.
- Language
 - A system of [...] used to represent and express [...] facts.

,Notation Language' is a ,tautology'





On Entity Relations


- Entity relation models are quite common in DB Design
- Q: Why do we need something new?
- A: Disconnected Entities





On ER Models

- Graphical Notation
- Great for humans
- Hard for machines







Requirements Relation Notation

- Support the six design principles
- Machine-interpretable and humanunderstandable.
- Support disconnected and remote entities, concepts and domains.
- Standard oriented.





Symbols, Objects and concepts

Allow sender and receiver to ,understand'

This lightbulb is made by ACME Corporation

This lightbulb is made by ACME Corporation subject predicate object

lightbulb:A is_made_by Corporation:ACME


What means ,lightbulb' or ,is_made_by' ?





Graphs

- Graph Theory
- Describes a relation between a subject and an object
- Nodes (vertices, points)
- Edges (lines, arcs)







A Graph Notation





Resource Description Framework

- W3C Specification from 1999
- making statements about uniquely identifiable resources in the form of ,subject-predicateobject', also known as ,triple'.
- URI (IRI) bounds it to namespaces
- Namespaces can serve as ,concept domain'





Vocabularies and Ontologies

- OWL (Web Ontology Language)
- Built on top of RDF

```
01 @prefix lb: <a href="http://notationexamples.irm/lightbulb#">http://notationexamples.irm/lightbulb#>.
02 @prefix co: <a href="http://notationexamples.irm/company">http://notationexamples.irm/company</a>*> .
03 @prefix pre: <a href="http://notationexamples.irm/relations#">http://notationexamples.irm/relations#</a>.
04 @prefix rdf: <a href="http://www.w3.org/1999/02/22-rdf-syntax-ns#">http://www.w3.org/1999/02/22-rdf-syntax-ns#</a>.
05 @prefix rdfs: <a href="http://www.w3.org/2000/01/rdf-schema#">http://www.w3.org/2000/01/rdf-schema#>.
06 @prefix owl: <a href="http://www.w3.org/2002/07/owl#>"> http://www.w3.org/2002/07/owl#>">
07
08 # three lightbulbs made by two different companies
09
10 lb:A pre:is made by co:ACME.
11 lb:B pre:is_made_by co:ACME.
12 lb:C pre:is_made_by co:BCME.
13
14 #describing the predicate is made by
15 pre:is_made_by rdf:type rdf:Property.
16 pre:is_made_by rdf:comment ",the relation between a product and its producer".
17 pre:is_made_by rdf:type owl:SymetricProperty.
18 pre:has_produced owl:inverseOf pre:is_made_by .
```





Query Language

- SQL is widely known
- SPARQL is the equivalent for ,triplestore' systems, aka ,Graph-Databases
- Allows for implicit and explicit queries

```
prefix lb: <a href="http://notationexamples.irm/lightbulb#">http://notationexamples.irm/lightbulb#</a>
prefix co: <a href="http://notationexamples.irm/company#">http://notationexamples.irm/company#</a>
prefix pre: <a href="http://notationexamples.irm/relations#">http://notationexamples.irm/relations#</a>
prefix rdf: <a href="http://www.w3.org/1999/02/22-rdf-syntax-ns#">http://www.w3.org/1999/02/22-rdf-syntax-ns#</a>
prefix rdfs: <a href="http://www.w3.org/2000/01/rdf-schema#">http://www.w3.org/2000/01/rdf-schema#</a>
prefix owl: <a href="http://www.w3.org/2002/07/owl#">http://www.w3.org/2002/07/owl#</a>

SELECT ?lightbulb WHERE {?lightbulb pre:is_made_by co:ACME .}
```





Query Language vs Notation

- SPARQL as query language, RDF/OWL as notation
 - standardized
 - machine interpretable (and still human readable with the help of ontologies)
 - supports disconnection (by caching the remote ontological definitions)
 - with the use of ontologies, it can provide any of the identified principles for IRM